

## Material Safety Data Sheet

**Material Name:** Tetrafluoromethane

MSDS ID: Hynote-0028

### Section 1 - Product and Company Identification

**Synonyms:** Halocarbon 14, Carbon tetrafluoride, Freon®14

**Chemical Name:** Tetrafluoromethane

**Formula:** CF<sub>4</sub>

**TDG (Canada) CLASSIFICATION:** 2.2

**WHMIS CLASSIFICATION:** A, D2B

#### ShangHai Hynote

906#, Tower A, Tomson Center,  
228 ZhangYang Road, PuDong,  
ShangHai, PRC.

#### EMERGENCY Telephone Numbers:

+86-21-58790001 (In South China):  
+86-379-65867058 (In North China)  
+86-10-110/119/120 (24 Hours)

**Product Information:** +86-379-65867058

**MSDS Information Email:** hynote@shtel.net.cn

### Section 2 - Composition/information on ingredients

**COMPOSITION:** >99.0%

PEL-OSHA<sup>1</sup>: None Established

**CAS NUMBER:** 75-73-0

TLV-ACGIH<sup>2</sup>: None Established

**RTECS#:** FG4920000

LD<sub>50</sub> or LC<sub>50</sub> Route/Species: Not Available

**Formula:** CF<sub>4</sub>

<sup>1</sup> As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993).

<sup>2</sup> As stated in the ACGIH 2004 Threshold Limit Values for Chemical Substances and Physical Agents.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

### Section 3 - Hazards Identification

#### EMERGENCY OVERVIEW

Colorless gas with ethereal odor. This product does not contain oxygen and may cause asphyxia if released in a confined area. Fluorocarbons may cause central nervous system depression and irregular heart beat at high concentrations. Contact with liquid may cause frostbite. Nonflammable but decomposes to toxic gases, including hydrofluoric acid, under fire conditions. Contents under pressure. Use and store below 125 °F.

**ROUTE OF ENTRY:**

Skin Contact	Skin Absorption	Eye Contact	Inhalation	Ingestion
Yes	No	Yes	Yes	No

**HEALTH EFFECTS:**

Exposure Limits No	Irritant Yes	Sensitization No
Teratogen No	Reproductive Hazard No	Mutagen No
Synergistic Effects None Reported		

Carcinogenicity:

NTP: No      IARC: No      OSHA: No

**EYE EFFECTS:**

PERSONS WITH POTENTIAL EXPOSURE SHOULD NOT WEAR CONTACT LENSES.

Contact with liquid may cause frostbite and tissue damage.

**SKIN EFFECTS:**

Contact with the rapidly evaporating liquid may cause frostbite. Frostbite effects appear as a change in color of the skin to grey or white, possibly followed by blistering.

**INGESTION EFFECTS:**

Ingestion is not likely.

**INHALATION EFFECTS:**

Product is relatively nontoxic. May cause minor irritation of the eyes, mucous membranes and respiratory system.

High concentrations may cause asphyxia from lack of oxygen or act as a narcotic causing central nervous system depression. Irregular heartbeat and sensitization of the heart to epinephrine may occur. Symptoms may include dizziness, disorientation, incoordination, narcosis, nausea or vomiting leading to unconsciousness.

Oxygen deficiency may occur in the presence of high concentrations resulting in asphyxiation.

Maintain oxygen levels at or above 19.5%.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:**

Pre-existing heart condition.

**POTENTIAL ENVIRONMENTAL EFFECTS:** Ecotoxicity values were unavailable. Toxic effects are expected to be similar to those seen in humans and test animals.

**Section 4- First Aid Measures**
**EYES:**

Never introduce ointment or oil into the eyes without medical advice! In case of freezing caused by rapidly evaporating liquid, DO NOT WASH THE EYES WITH HOT OR EVEN TEPID WATER! Remove victim from the source of contamination. For contact with small amounts of liquid, open the eyelids wide to allow the liquid to evaporate. For contact with large amounts, rinse with a low pressure stream of cool water for 15 minutes. Refer the victim to an ophthalmologist for treatment and follow up. If the victim cannot tolerate light, protect the eyes with dark glasses. The use of bandages is not recommended as keeping the eyelids closed or exerting pressure on the eyelid may cause further damage.

**SKIN:**

For dermal contact or frostbite: Remove contaminated clothing and flush affected areas with lukewarm water. DO NOT USE HOT WATER. A physician should see the patient promptly if contact with the product has resulted in frostbite.

**INGESTION:**

Unlikely as product is a gas at room temperature.

**INHALATION:**

PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS. Remove victim to fresh air. Administer artificial respiration if breathing has stopped and supplement with oxygen by a trained individual. Further treatment should be symptomatic and supportive. Seek medical attention as soon as possible for follow up treatment. Remove to fresh air. If necessary, give oxygen or provide artificial respiration. Call a physician. NOTE TO PHYSICIAN: A patient adversely affected by exposure to this product should not be given adrenaline (epinephrine) or similar heart stimulant since these would increase the risk of cardiac arrhythmias.

**Section 5- Fire-Fighting Measures**

Conditions of Flammability: Nonflammable		
Flash point: None	Method: Not Applicable	Autoignition Temperature: None
LEL(%): None	UEL(%): None	
Hazardous combustion products: None		
Sensitivity to mechanical shock: None		
Sensitivity to static discharge: None		

**FIRE AND EXPLOSION HAZARDS:**

If involved in a fire, product may decompose yielding toxic products, which may include phosgene, hydrochloric and hydrofluoric acids. Cylinder may vent rapidly or rupture violently from pressure when involved in a fire situation.

**EXTINGUISHING MEDIA:**

None required. Use media appropriate for surrounding flammable substances.

**FIRE FIGHTING INSTRUCTIONS:**

Firefighters should wear respiratory protection (SCBA) and full turnout or Bunker gear with chemical protective clothing as necessary to prevent exposure to decomposition products. Continue to cool fire-exposed cylinders until well after flames are extinguished.

**Section 6- Accidental Release Measures**

Evacuate all personnel from affected area. Use appropriate protective equipment (See Section 8). Stop the flow of gas or remove cylinder to outdoor location if this can be done without risk. Ventilate enclosed areas. If leak is in user's equipment, be certain to purge piping with inert gas prior to attempting repairs. If leak is in container or container valve, contact the appropriate emergency telephone number listed in Section 1 or call your closest Hynote location.

**Section 7- Handling and Storage**

Product is noncorrosive and may be used with any common structural material. Silver and carbon bearing alloys can act as catalysts for decomposing the product at high temperatures. Alloys containing more than 2% magnesium should not be used if water is present.

Use only in well-ventilated areas. Valve protection caps must remain in place unless container is secured with valve outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement.

Use a pressure reducing regulator when connecting cylinder to lower pressure piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder. Protect cylinders from physical damage. Do not insert any object (i.e.: screwdriver) into valve cap openings as this can damage the valve causing leakage.

Store in cool, dry, well-ventilated area of non-combustible construction away from heavily trafficked areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 125oF (52oC). Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in-first out" inventory system to prevent full cylinders being stored for excessive periods of time. For additional handling recommendations, consult Compressed Gas Association Pamphlet P-1. Never carry a compressed gas cylinder or a container of a gas in cryogenic liquid form in an enclosed space such as a car trunk, van or station wagon. A leak can result in a fire, explosion, asphyxiation or a toxic exposure.

**Section 8- Exposure Controls/Personal Protection****ENGINEERING CONTROLS:**

Local exhaust used in combination with general ventilation as necessary to control air contaminants to at or below acceptable exposure guidelines.

**EYE/FACE PROTECTION:**

Safety glasses for gas. Protective goggles with face shield for liquid.

**SKIN PROTECTION:**

Protective gloves suitable for the job. Insulated gloves for handling liquid.

**RESPIRATORY PROTECTION:**

For emergency release use a positive pressure NIOSH approved airsupplying respirator systems (SCBA or airline/escape bottle) using a full-face mask and at a minimum Grade D air.

**OTHER/GENERAL PROTECTION:**

Safety shoes, eyewash station.

**Section 9- Physical and Chemical Properties**

<b>PARAMETER</b>	<b>VALUE</b>	<b>UNITS</b>
Physical state (gas, liquid, solid)	: Gas	
Vapor pressure at 70 °F	: 445	psia
Vapor density at 70 °F (Air = 1)	: 3.04	
Evaporation point	: Not Available	
Boiling point	: -198.4	°F
	: -128	°C
Freezing point	: -299	°F
	: -184	°C
pH	: Not Applicable	
Specific gravity	: Not Applicable	
Oil/water partition coefficient	: Not Available	
Solubility (H2O)	: Negligible	
Odor threshold	: Not Available	
Odor and appearance	: Colorless gas with slight ethereal odor at concentrations greater than 20% by volume..	

**Section 10- Stability and Reactivity**

**STABILITY:**

Stable

**INCOMPATIBLE MATERIALS:**

May react violently with chemically active metals such as sodium, potassium and barium, powdered magnesium, powdered aluminum and organometallics.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Decomposes at fire temperatures to hydrochloric and hydrofluoric acids, carbonyl fluoride and phosgene.

**HAZARDOUS POLYMERIZATION:**

Will not occur.

**Section 11- Toxicological Information**

**INHALATION:** Tetrafluoromethane is narcotic at high concentrations and may cause myocardial sensitization and ventricular fibrillation.

**SKIN AND EYE:** May cause minor irritation. Repeated contact may defat skin.

**OTHER:** No OSHA PEL or ACGIH TLV has been established for this substance.

**Section 12- Ecological Information**

Not classified as a Class I or II Ozone depleting substance. It is stable in the atmosphere with a half-life for degradation via photochemically-produced hydroxyl radicals of > 110 years. The estimated atmospheric lifetime ranges from 10,000 to 50,000 years. The estimated BCF of 1.6 suggests a low potential for bioconcentration in aquatic organisms.

**Section 13- Disposal Considerations**

Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container PROPERLY LABELED, WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE to Hynote or authorized distributor for proper disposal.

**Section 14- Transport Information**

**DOT/IMO SHIPPING NAME:** Tetrafluoromethane, Compressed or Refrigerant Gas R14

**HAZARD CLASS:** 2.2

**IDENTIFICATION NUMBER:** UN 1982

**PRODUCT RQ:** None

**SHIPPING LABEL(s):** NONFLAMMABLE GAS

**PLACARD (when required):** NONFLAMMABLE GAS

**Section 15- Regulatory Information****SARA TITLE III NOTIFICATIONS AND INFORMATION****SARA TITLE III - HAZARD CLASSES:**

Acute Health Hazard

Sudden release of Pressure Hazard

**SARA TITLE III – SECTION 313 SUPPLIER NOTIFICATION:**

This product does not contain toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and 40 CFR 372.

**U.S. TSCA/Canadian DSL:** All ingredients are listed on the U.S. Toxic Substances Control Act (TSCA) inventory or exempt from listing and on the Canadian Domestic Substance List (DSL).

**California Proposition 65:** This product does not contain ingredient(s) known to the State of California to cause cancer or reproductive toxicity.

**Canadian Controlled Products Regulations (CPR):** This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

**Section 16- Other Information**

NFPA HAZARD CODES	HMIS HAZARD CODES	RATINGS SYSTEM
Health: 1	Health: 0	0 = No Hazard
Flammability: 0	Flammability: 0	1 = Slight Hazard
Instability: 0	Physical Hazard: 3	2 = Moderate Hazard
		3 = Serious Hazard
		4 = Severe Hazard

Note: Ratings were assigned in accordance with Compressed Gas Association (CGA) guidelines as published in CGA Pamphlet P-19-2004, CGA Recommended Hazard Ratings for Compressed Gases, 2<sup>nd</sup> Edition.

ACGIH	American Conference of Governmental Industrial Hygienists
DOT	Department of Transportation
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
SARA	Superfund Amendments and Reauthorization Act
STEL	Short Term Exposure Limit
TDG	Transportation of Dangerous Goods
TLV	Threshold Limit Value
WHMIS	Workplace Hazardous Materials Information System

Compressed gas cylinders shall not be refilled without the express written permission of the owner. Shipment of a compressed gas cylinder which has not been filled by the owner or with his/her (written) consent is a violation of transportation regulations.

**DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).



**NOTICE TO READER:**

ALTHOUGH THE INFORMATION CONTAINED IN THIS DOCUMENT IS PRESENTED IN GOOD FAITH, BASED ON AVAILABLE INFORMATION BELIEVED TO BE RELIABLE AT THE TIME OF PREPARATION OF THIS DOCUMENT, SHANGHAI HYNOTE MAKES NO WARRANTIES OR REPRESENTATIONS WITH RESPECT TO THE INFORMATION OR THE PRODUCT/MATERIALS DESCRIBED HEREIN, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES AND CONDITIONS (INCLUDING ALL WARRANTIES AND CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE). NO FREEDOM FROM INFRINGEMENT OF ANY PATENT OWNED BY SHANGHAI HYNOTE OR OTHERS IS TO BE INFERRED.

THIS INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE. PLEASE CONTACT SHANGHAI HYNOTE FOR THE MOST CURRENT VERSION OF THIS MSDS. SHANGHAI HYNOTE DOES NOT ASSUME RESPONSIBILITY FOR MSDS OBTAINED FROM THIRD PARTY SOURCES. UNLESS SPECIFICALLY AGREED OTHERWISE, SHANGHAI HYNOTE DOES NOT TAKE RESPONSIBILITY FOR USE, TRANSPORTATION, STORAGE, HANDLING OR DISPOSAL, OF THE PRODUCTS DESCRIBED HEREIN.