

## Material Safety Data Sheet

**Material Name:** Hydrogen Sulfide

MSDS ID: Hynote-0040

### Section 1 - Product and Company Identification

**Synonyms:** Dihydrogen Sulfide, Sulfur Hydride

**Chemical Name:** Hydrogen Sulfide

**Formula:** H<sub>2</sub>S

**TDG (Canada) CLASSIFICATION:** 2.3 (2.1)

**WHMIS CLASSIFICATION:** A, B1, D1A, D2B

#### ShangHai Hynote

906#, Tower A, Tomson Center,  
228 ZhangYang Road, PuDong,  
ShangHai, PRC.

#### EMERGENCY Telephone Numbers:

+86-21-58790001 (In South China):  
+86-379-65867058 (In North China)  
+86-10-110/119/120 (24 Hours)

**Product Information:** +86-379-65867058

**MSDS Information Email:** hynote@shtel.net.cn

### Section 2 - Composition/information on ingredients

**COMPOSITION:** 99.9%

PEL-OSHA<sup>1</sup>: 20 ppm Ceiling

**CAS NUMBER:** 7783-06-4

TLV-ACGIH<sub>2</sub>: 10 ppm TWA, 15 ppm STEL

**RTECS#:** MX1225000

LD<sub>50</sub> or LC<sub>50</sub> Route/Species: LC<sub>50</sub> 444ppm (rat)

**Formula:** H<sub>2</sub>S

<sup>1</sup> As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993).

<sup>2</sup> As stated in the ACGIH 1994-95 Threshold Limit Values for Chemical Substances and Physical Agents.

### Section 3 - Hazards Identification

#### EMERGENCY OVERVIEW

Irritating to the eyes, mucous membranes and respiratory system. Inhaled gas inhibits cellular respiration resulting in pulmonary paralysis, sudden collapse and death. Extremely flammable.

#### ROUTE OF ENTRY:

Skin Contact	Skin Absorption	Eye Contact	Inhalation	Ingestion
Yes	No	Yes	Yes	Yes

**HEALTH EFFECTS:**

Exposure Limits Yes	Irritant Yes	Sensitization No
Teratogen Yes	Reproductive Hazard Yes	Mutagen No
Synergistic Effects None Reported		

Carcinogenicity:

NTP:No      IARC: No      OSHA: No

**EYE EFFECTS:**

Low concentrations will generally cause irritation to the conjunctiva. Repeated exposure to low concentrations is reported to cause conjunctivitis, photo phobia, corneal bullae, tearing, pain and blurred vision.

**SKIN EFFECTS:**

May irritate the skin upon contact.

**INGESTION EFFECTS:**

Ingestion is unlikely. Hydrogen sulfide will irritate the mucous membranes causing a burning feeling with excess salivation likely. Irritation of the gastrointestinal tract may also occur.

**INHALATION EFFECTS:**

Hydrogen sulfide reacts with enzymes in the bloodstream and inhibits cellular respiration resulting in pulmonary paralysis, sudden collapse and death. Continuous exposure to low (15-50 ppm) concentrations will generally cause irritation to mucous membranes, and may also cause headache, dizziness or nausea. Higher concentrations (200-300 ppm) may result in respiratory arrest leading to coma or unconsciousness. Exposures for more than 30 minutes at concentrations greater than 700 ppm have been fatal.

Continuous inhalation of low concentrations may cause olfactory fatigue or paralysis of the sense of smell. Thus, detection of hydrogen sulfide by its odor is not effective.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:**

Blood disorders.

**NFPA HAZARD CODES**

Health: 4  
Flammability: 4  
Reactivity: 0

**HMIS HAZARD CODES**

Health: 4  
Flammability: 4  
Reactivity: 0

**RATINGS SYSTEM**

0 = No Hazard  
1 = Slight Hazard  
2 = Moderate Hazard  
3 = Serious Hazard  
4 = Severe Hazard

**Section 4- First Aid Measures**
**EYES:**

PERSONS WITH POTENTIAL EXPOSURE TO HYDROGEN SULFIDE SHOULD NOT WEAR CONTACT LENSES. Flush contaminated eyes with large amounts of water for at least 15 minutes. Part eyelids with fingers to ensure complete flushing. If irritation persists, seek medical attention immediately.

**SKIN:**

Flush affected area with water. If irritation persists, consult a physician.

**INGESTION:**

Treat in a manner similar to inhalation exposure. Seek medical attention as soon as possible.

**INHALATION:**

PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS AND SHOULD RECOGNIZE THE HAZARDS OF OVEREXPOSURE DUE TO OLFACTORY FATIGUE. An extreme fire hazard exists when rescuing semiconscious or unconscious persons due to the flammability hazard.

Avoid use of rescue equipment which may contain ignition sources or cause static discharge.

Victims should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. If breathing has stopped administer artificial resuscitation and supplemental oxygen or a mixture of 5% carbon dioxide in oxygen. Keep victim calm and warm. Further treatment should be symptomatic and supportive. Seek medical assistance immediately.

**Section 5- Fire-Fighting Measures**

Conditions of Flammability: Nonflammable		
Flash point: None	Method: Not Applicable	Autoignition Temperature: 554 ° F (290 °C)
LEL(%): 4.0		UEL(%):44.0
Hazardous combustion products: Sulfur Compounds		
Sensitivity to mechanical shock: None		
Sensitivity to static discharge: None		

**FIRE AND EXPLOSION HAZARDS:**

Hydrogen sulfide is heavier than air and may accumulate in low areas and may travel a considerable distance to a source of ignition. Should flame be extinguished and flow of gas continue, increase ventilation to prevent flammable mixture formation in low areas or pockets. Product may explode or burn over a wide range of mixtures in air.

**EXTINGUISHING MEDIA:**

Water, carbon dioxide, dry chemicals.

**FIRE FIGHTING INSTRUCTIONS:**

If possible, stop the flow of hydrogen sulfide. Use water spray to cool surrounding containers. Fire fighters should use self-contained breathing apparatus.



**Section 6- Accidental Release Measures**

Evacuate all personnel from affected area. Use appropriate protective equipment. If leak is in user’s equipment, be certain to purge piping with inert gas prior to attempting repairs. If leak is in container or container valve, contact the appropriate emergency telephone number listed in Section 1 or call your closest Hynote location.

**Section 7- Handling and Storage**

Earth-ground and bond all lines and equipment associated with the Hydrogen Sulfide system. All electrical equipment should be non-sparking or explosion proof.

Do not rely on the olfactory sense to detect the presence of hydrogen sulfide. Analytical devices and instrumentation are readily available for this purpose. Perform frequent analytical tests to be certain that the TWA is not exceeded. Many metals corrode rapidly with wet hydrogen sulfide.

Anhydrous hydrogen sulfide can be handled in carbon steel, aluminum Inconel®, Stellite® and 304 and 316 stainless steels. Avoid hard steels which are highly stressed since they may be susceptible to hydrogen embrittlement from hydrogen sulfide.

Use only in well-ventilated areas. Valve protection caps must remain in place unless container is secured with valve outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure reducing regulator when connecting cylinder to lower pressure (<750 psig) piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the system.

Protect cylinders from physical damage. Store in cool, dry, well-ventilated area away from heavily trafficked areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 130 °F (54°C).

Cylinders should be stored upright and firmly secured to prevent falling or being knocked over.

Full and empty cylinders should be segregated. Use a "first in-first out" inventory system to prevent full cylinders being stored for excessive periods of time. Post "NO SMOKING OR OPEN FLAMES" signs in the storage area or use area.

There should be no sources of ignition in the storage or use area. For additional storage recommendations, consult Compressed Gas Association Pamphlets P-1 and G-12.

Never carry a compressed gas cylinder or a container of a gas in cryogenic liquid form in an enclosed space such as a car trunk, van or station wagon. A leak can result in a fire, explosion, asphyxiation or a toxic exposure.

**Section 8- Exposure Controls/Personal Protection**

**EXPOSURE LIMITS<sup>1</sup>:**

INGREDIENT	%VOLUME	PEL-OSHA <sup>2</sup>	TLV-ACGIH <sup>3</sup>	LD <sub>50</sub> or LC <sub>50</sub> Route/Species
Hydrogen Sulfide Formula: H <sub>2</sub> S CAS: 7783-06-4 RTECS#: MX1225000	99.9	20 ppm Ceiling	10 ppm TWA 15 ppm STEL	LC <sub>50</sub> 444 ppm (rat)

<sup>1</sup> Refer to individual state of provincial regulations, as applicable, for limits which may be more stringent than those listed here.

<sup>2</sup> As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993)

<sup>3</sup> As stated in the ACGIH 1994-1995 Threshold Limit Values for Chemical Substances and Physical Agents.

**ENGINEERING CONTROLS:**

Hood with forced ventilation. Use local exhaust to prevent accumulation above exposure limit.

**EYE/FACE PROTECTION:**

Gas tight chemical goggles or full-face piece respirator.

**SKIN PROTECTION:**

Protective gloves: Neoprene, butyl rubber, PVC, polyethylene.

**RESPIRATORY PROTECTION:**

Positive pressure air line with full-face mask and escape bottle or self-contained breathing apparatus should be available for emergency use.

**OTHER/GENERAL PROTECTION:**

Safety shoes, safety shower, eyewash "fountain".

**Section 9- Physical and Chemical Properties**

<b>PARAMETER</b>	<b>VALUE</b>	<b>UNITS</b>
Physical state (gas, liquid, solid)	: Vapor	
Vapor pressure	: 267(1840kPa)	psia
Vapor density at STP (Air = 1)	: 1.21	
Evaporation point	: Not Available	
Boiling point	: -76	°F
	: -60	°C
Freezing point	: -117.8	°F
	: -82.2	°C
pH	: Not Applicable	
Specific gravity	: Not Available	
Oil/water partition coefficient	: Not Available	
Solubility (H <sub>2</sub> O)	: Soluble	
Odor threshold	: Not Applicable	
Odor and appearance	: Colorless vapor with rotten egg odor.	

**Section 10- Stability and Reactivity**

**STABILITY:**

Stable.

**INCOMPATIBLE MATERIALS**

Dangerously reactive when mixed with concentrated nitric acid or other strong oxidizing agents.

Vapors will ignite spontaneously when mixed with vapors of chlorine, oxygen difluoride or nitrogen trifluoride.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Oxides of sulfur.

**HAZARDOUS POLYMERIZATION:**

Does not occur.

**Section 11- Toxicological Information****REPRODUCTIVE:**

Toxic effects observed in newborn rats after exposure of pregnant female to 20 ppm Hydrogen Sulfide.

**Section 12- Ecological Information**

No data given.

**Section 13- Disposal Considerations**

Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container PROPERLY LABELED, WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE to HYNOTE or authorized distributor for proper disposal.

**Section 14- Transport Information**

**DOT/IMO SHIPPING NAME:** Hydrogen Sulfide

**HAZARD CLASS:** 2.3

**IDENTIFICATION NUMBER:** UN 1053

**PRODUCT RQ:** None

**SHIPPING LABEL(s):** POISON GAS, FLAMMABLE GAS

**PLACARD (when required):** POISON GAS, FLAMMABLE GAS

**Section 15- Regulatory Information**

Hydrogen sulfide is listed under the accident prevention provisions of section 112(r) of the Clean Air Act (CAA) with a threshold quantity (TQ) of 10,000 pounds.

**SARA TITLE III NOTIFICATIONS AND INFORMATION**

Hydrogen sulfide is listed as an extremely hazardous substance (EHS) subject to state and local reporting under Section 304 of SARA Title III (EPCRA).

The presence of hydrogen sulfide in quantities in excess of the threshold planning quantity (TPQ) of 100 pounds requires certain emergency planning activities to be conducted.

Releases of hydrogen sulfide in quantities equal to or greater than the reportable quantity (RQ) of 100 pounds are subject to reporting to the National Response Center under CERCLA, Section 304 SARA Title III.

**SARA TITLE III - HAZARD CLASSES:**

Acute Health Hazard  
Chronic Health Hazard  
Fire Hazard  
Sudden Release of Pressure Hazard

**SARA TITLE III - SECTION 313 SUPPLIER NOTIFICATION:**

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the

Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372:

CAS NUMBER	INGREDIENT NAME	PERCENT BY VOLUME
7783-06-4	Hydrogen sulfide	> 99.9

This information must be included on all MSDS that are copied and distributed for this material.

**Section 16- Other Information**

Compressed gas cylinders shall not be refilled without the express written permission of the owner.

Shipment of a compressed gas cylinder which has not been filled by the owner or with his/her (written) consent is a violation of transportation regulations.

**DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

**NOTICE TO READER:**

ALTHOUGH THE INFORMATION CONTAINED IN THIS DOCUMENT IS PRESENTED IN GOOD FAITH, BASED ON AVAILABLE INFORMATION BELIEVED TO BE RELIABLE AT THE TIME OF PREPARATION OF THIS DOCUMENT, SHANGHAI HYNOTE MAKES NO WARRANTIES OR REPRESENTATIONS WITH RESPECT TO THE INFORMATION OR THE PRODUCT/MATERIALS DESCRIBED HEREIN, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES AND CONDITIONS (INCLUDING ALL WARRANTIES AND CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE). NO FREEDOM FROM INFRINGEMENT OF ANY PATENT OWNED BY SHANGHAI HYNOTE OR OTHERS IS TO BE INFERRED.

THIS INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE. PLEASE CONTACT SHANGHAI HYNOTE FOR THE MOST CURRENT VERSION OF THIS MSDS. SHANGHAI HYNOTE DOES NOT ASSUME RESPONSIBILITY FOR MSDS OBTAINED FROM THIRD PARTY SOURCES. UNLESS SPECIFICALLY AGREED OTHERWISE, SHANGHAI HYNOTE DOES NOT TAKE RESPONSIBILITY FOR USE, TRANSPORTATION, STORAGE, HANDLING OR DISPOSAL, OF THE PRODUCTS DESCRIBED HEREIN.



HYNOTE GAS

---