



Material Safety Data Sheet

Material Name: Krypton

MSDS ID: Hynote-0030

Section 1 - Product and Company Identification

Synonyms: Krypton, compressed

Chemical Name: Krypton

Formula: Kr

TDG (Canada) CLASSIFICATION: 2.2

WHMIS CLASSIFICATION: A

ShangHai Hynote

906#, Tower A, Tomson Center,
228 ZhangYang Road, PuDong,
ShangHai, PRC.

EMERGENCY Telephone Numbers:

+86-21-58790001 (In South China):
+86-379-65867058 (In North China)
+86-10-110/119/120 (24 Hours)

Product Information: +86-379-65867058

MSDS Information Email: hynote@shtel.net.cn

Section 2 - Composition/information on ingredients

COMPOSITION: 99.95 to 99.995%

PEL-OSHA¹: Simple Asphyxiant

CAS NUMBER: 7439-90-9

TLV-ACGIH²: Simple Asphyxiant

RTECS#: Not Available

LD₅₀ or LC₅₀ Route/Species: Not Available

Formula: Kr

¹ As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993).

² As stated in the ACGIH 1994-95 Threshold Limit Values for Chemical Substances and Physical Agents.

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Simple Asphyxiant - This product does not contain oxygen and may cause asphyxia if released in a confined area. Maintain oxygen levels above 19.5%. Nonflammable.

ROUTE OF ENTRY:

Skin Contact	Skin Absorption	Eye Contact	Inhalation	Ingestion
No	No	No	Yes	No

**HEALTH EFFECTS:**

Exposure Limits No	Irritant No	Sensitization No
Teratogen No	Reproductive Hazard No	Mutagen No
Synergistic Effects None Reported		

Carcinogenicity:

NTP: No

IARC: No

OSHA: No

EYE EFFECTS:

None known.

SKIN EFFECTS:

None known.

INGESTION EFFECTS:

None known. Ingestion is unlikely as product is gas at room temperature.

INHALATION EFFECTS:

Product is a non-toxic simple asphyxiant. High concentrations may exclude an adequate supply of oxygen to the lungs. Effect of oxygen deficiency resulting from simple asphyxiants may include: rapid breathing, diminished mental alertness, impaired muscular coordination, faulty judgement, depression of all sensations, emotional instability, and fatigue. As asphyxiation progresses, nausea, vomiting, prostration, and loss of consciousness may result, eventually leading to convulsions, coma, and death.

Oxygen deficiency during pregnancy has produced developmental abnormalities in humans and experimental animals.

NFPA HAZARD CODES

Health: 0

Flammability: 0

Reactivity: 0

HMIS HAZARD CODES

Health: 0

Flammability: 0

Reactivity: 0

RATINGS SYSTEM

0 = No Hazard

1 = Slight Hazard

2 = Moderate Hazard

3 = Serious Hazard

4 = Severe Hazard

Section 4- First Aid Measures**EYES:**

None required.

SKIN EFFECTS:

None required.

INGESTION:

None required.

INHALATION:

PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS. Victims should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Unconscious persons should be moved to an uncontaminated area, and if breathing has stopped, administer artificial resuscitation and supplemental oxygen. Further treatment should be symptomatic and supportive.

Section 5- Fire-Fighting Measures

Conditions of Flammability: Flammable gas		
Flash point: None	Method: Not Applicable	Autoignition Temperature: None
LEL(%): None	UEL(%): None	
Hazardous combustion products: None		
Sensitivity to mechanical shock: None		
Sensitivity to static discharge: None		

FIRE AND EXPLOSION HAZARDS:

None. Nonflammable.

EXTINGUISHING MEDIA:

None required. Use as appropriate for surrounding materials.

Section 6- Accidental Release Measures

Evacuate all personnel from affected area. Use appropriate protective equipment. If leak is in container or container valve, contact the appropriate emergency telephone number listed in Section 1 or call your closest Hynote location.

Section 7- Handling and Storage**Electrical Classification:**

Non-hazardous.

This gas mixture is noncorrosive and may be used with all common structural materials.

Use only in well-ventilated areas. Valve protection caps must remain in place unless container is secured with valve protection outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.



Protect cylinders from physical damage. Store in cool, dry, well-ventilated area of non-combustible construction away from heavily trafficked areas and emergency exits.

Do not allow the temperature where cylinders are stored to exceed 125°F (52°C). Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Use a "first in-first out" inventory system to prevent full cylinders being stored for excessive periods of time. For additional recommendations, consult Compressed Gas Association Pamphlets P-1, P-14, P-9, and Safety Bulletin SB-2.

Never carry a compressed gas cylinder or a container of a gas in cryogenic liquid form in an enclosed space such as a car trunk, van or station wagon. A leak can result in a fire, explosion, asphyxiation or a toxic exposure.

Section 8- Exposure Controls/Personal Protection

EXPOSURE LIMITS¹:

INGREDIENT	%VOLUME	PEL-OSHA ²	TLV-ACGIH ³	LD ₅₀ or LC ₅₀ Route/Species
Krypton Formula: Kr CAS: 7439-90-9 RTECS#:N/A	99.95 to 99.995	Simple Asphyxiant	Simple Asphyxiant	Not Available

¹ Refer to individual state or provincial regulations, as applicable, for limits which may be more stringent than those listed here.

² As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993)

³ As stated in the ACGIH 1994-1995 Threshold Limit Values for Chemical Substances and Physical Agents.

ENGINEERING CONTROLS:

Local exhaust to prevent accumulation of high concentrations so as to reduce the oxygen level in the air to less than 19.5%.

EYE/FACE PROTECTION:

Safety goggles or glasses as appropriate for the job.

SKIN PROTECTION:

Protective gloves of material appropriate for the job.

RESPIRATORY PROTECTION:

Positive pressure air line with full-face mask and escape bottle or self-contained breathing apparatus should be available for emergency use.

OTHER/GENERAL PROTECTION:

Safety shoes or other footwear as appropriate for the job.



Section 9- Physical and Chemical Properties

PARAMETER	VALUE	UNITS
Physical state (gas, liquid, solid)	: Gas	
Vapor pressure at STP	: Not Available	
Vapor density (Air = 1)	: 2.92	
Evaporation point	: Not Available	
Boiling point	: -244	°F
	: -153.3	°C
Freezing point	: -250.9	°F
	: -157.2	°C
pH	: Not Applicable	
Specific gravity	: Not Available	
Oil/water partition coefficient	: Not Available	
Solubility (H ₂ O)	: Negligible	
Odor threshold	: Not Applicable	
Odor and appearance	: An Odorless, colorless gas	

Section 10- Stability and Reactivity

STABILITY:

Stable

INCOMPATIBLE MATERIALS:

None

HAZARDOUS POLYMERIZATION:

Will not occur.

Section 11- Toxicological Information

Oxygen deficiency during pregnancy has produced developmental abnormalities in humans and experimental animals.

No data given in the Registry of Toxic Effects of Chemical Substances (RTECS) or Sax, Dangerous Properties of Industrial Materials, 7th ed.

Section 12- Ecological Information

No data given.

Section 13- Disposal Considerations

Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container PROPERLY LABELED, WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE to Hynote or authorized distributor for proper disposal.



Section 14- Transport Information

DOT/IMO SHIPPING NAME: Krypton, compressed

HAZARD CLASS: 2.2

IDENTIFICATION NUMBER: UN 1056

PRODUCT RQ: None

SHIPPING LABEL(s): NONFLAMMABLE GAS

PLACARD (when required): NONFLAMMABLE GAS

Section 15- Regulatory Information

SARA TITLE III NOTIFICATIONS AND INFORMATION

SARA TITLE III - HAZARD CLASSES:

Sudden Release of Pressure Hazard

Section 16- Other Information

Compressed gas cylinders shall not be refilled without the express written permission of the owner.

Shipment of a compressed gas cylinder which has not been filled by the owner or with his/her (written) consent is a violation of transportation regulations.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

NOTICE TO READER:

ALTHOUGH THE INFORMATION CONTAINED IN THIS DOCUMENT IS PRESENTED IN GOOD FAITH, BASED ON AVAILABLE INFORMATION BELIEVED TO BE RELIABLE AT THE TIME OF PREPARATION OF THIS DOCUMENT, SHANGHAI HYNOTE MAKES NO WARRANTIES OR REPRESENTATIONS WITH RESPECT TO THE INFORMATION OR THE PRODUCT/MATERIALS DESCRIBED HEREIN, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES AND CONDITIONS (INCLUDING ALL WARRANTIES AND CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE). NO FREEDOM FROM INFRINGEMENT OF ANY PATENT OWNED BY SHANGHAI HYNOTE OR OTHERS IS TO BE INFERRED.

THIS INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE. PLEASE CONTACT SHANGHAI HYNOTE FOR THE MOST CURRENT VERSION OF THIS MSDS. SHANGHAI



HYNOTE GAS

HYNOTE DOES NOT ASSUME RESPONSIBILITY FOR MSDS OBTAINED FROM THIRD PARTY SOURCES. UNLESS SPECIFICALLY AGREED OTHERWISE, SHANGHAI HYNOTE DOES NOT TAKE RESPONSIBILITY FOR USE, TRANSPORTATION, STORAGE, HANDLING OR DISPOSAL, OF THE PRODUCTS DESCRIBED HEREIN.